A Note on the Approximation Error of Top-k Attention Routing

Your Name

November 13, 2026

Abstract

We give a short bound on the approximation error introduced by restricting attention to the top-k highest-scoring keys, showing the error decays exponentially in the score gap γ between selected and discarded keys.

1 Setup

Let $q \in \mathbb{R}^d$ be a query and $k_1, \ldots, k_n$ the key vectors for a sequence of length n. Define attention weights

$$\alpha_i = \frac{\exp(q \cdot k_i/\sqrt{d})}{\sum_{j=1}^{n} \exp(q \cdot k_j/\sqrt{d})}.$$

Let $S \subset \{1, \ldots, n\}$, $|S| = k$, be the indices of the k largest scores $q \cdot k_i$, and let $\tilde{\alpha}$ denote the renormalized weights restricted to S.

2 Main Result

Assume the scores $q \cdot k_i/\sqrt{d}$ outside S are all at least $\gamma > 0$ below $\min_{i \in S} q \cdot k_i/\sqrt{d}$. Then the total variation distance between α and its zero-padded restriction satisfies

$$\|\alpha - \tilde{\alpha}\|_{TV} \leq (n-k)\, e^{-\gamma} \tag{1}$$

$$\to 0 \quad \text{as } \gamma \to \infty. \tag{2}$$

The bound shows that whenever the score gap γ between selected and discarded keys grows with $\log n$, the truncation error vanishes even as sequence length increases.

3 Discussion

In practice, learned routing improves on random or fixed selection precisely because it increases the effective gap γ between retained and discarded keys. This suggests routing quality, not merely sparsity ratio, is the primary lever for controlling approximation error.